

IN THE CLAIMS:

---

1. (Currently Amended) A structure in which a plurality of electrical equipments are arranged in a motor vehicle, comprising:  
an engine control computer, a relay block, a junction box, and an ABS actuator;  
a brake booster which is located at one of a right half region and a left half region of the vehicle; and

7-1  
a vehicle body with a longitudinal centerline that defines a space including a generally centralized region as viewed in a direction of the width of the vehicle, said region extending symmetrically from both sides of the centerline for a distance which is no more than one-half the distance, measured in a direction normal to the centerline, between the centerline and a longitudinal axis of the brake booster disposed within the vehicle body,

wherein the engine control computer, relay block, junction box, and ABS actuator are concentrated in said generally central region of the space defined by the vehicle body, and the locations of the engine control computer, the relay block, the junction box and the ABS actuator are the same when the vehicle is a right-hand drive vehicle as when the vehicle is a left-hand drive vehicle,

wherein said vehicle body includes a partition wall that separates an engine room and a cabin from each other, and the engine control computer, the relay block and the ABS actuator are located on an engine-room side of the partition wall.

2. (Original) The structure of claim 1, wherein said vehicle body includes a partition wall that separates an engine room and a cabin from each other, and wherein the relay block and the junction box are concentrated in said generally central region as viewed in the vehicle width direction, to be located in the vicinity of the partition wall.

3. (Original) The structure as defined in claim 2, wherein said vehicle body includes a cowl formed therein, and wherein at least one of the relay block and the junction box is located in the cowl.

4. (Original) The structure as defined in claim 2, wherein the relay block and the junction box are formed as an integral assembly.

5. (Original) The structure as defined in claim 4, wherein said vehicle body includes a cowl formed therein, and wherein at least a part of the integral assembly of the relay block and the junction box is located in the cowl.

6. (Original) The structure as defined in claim 1, wherein the engine control computer is located in a generally central region of the engine room as viewed in the vehicle width direction.

7. (Original) The structure as defined in claim 1, wherein said vehicle body includes a dash cross member that substantially extends in the vehicle width direction, and wherein the ABS actuator is located on a generally central portion of the dash cross member as viewed in the vehicle width direction.

8. (Original) The structure as defined in claim 1, wherein the meter unit is located in a generally central region of the cabin as viewed in the vehicle width direction.

9. (Canceled).

9 10. (Previously presented) A structure in which a plurality of electrical equipments are arranged in a motor vehicle, comprising:

an engine control computer, a relay block, a junction box, and an ABS actuator;  
and

FI a vehicle body with a longitudinal centerline that defines a space including a generally centralized region as viewed in a direction of the width of the vehicle, said region extending symmetrically about the centerline and having a total width of one-half of the vehicle width,

wherein the engine control computer, relay block, junction box, and ABS actuator are concentrated in said generally central region of the space defined by the vehicle body,

wherein said vehicle body includes a partition wall that separates an engine room and a cabin from each other, and the engine control computer, the relay block and the ABS actuator are located on an engine-room side of the partition wall.

---